



#### **Fanfold or roll media**

The CL-S400DT can handle fanfold tickets as well as standard roll media for labels or receipts.

#### **Easy read LCD panel**

The LCD panel allows quick and simple configuration and also flashes red when an error occurs quickly alerting the operator.

#### **Environmentally friendly**

From production and packaging to utilisation and recycling the CL-S400DT fulfills today's demand for green IT products. The integrated ENERGY STAR® power supply is one of the most efficient at managing power consumption.

#### **Applications**

- Courier
- Retail
- Logistic / Transport
- Ticketing
- Kiosk
- Betting



Performance ticket and label printing



With a USB and serial interface on board the CT-S400DT is a future-proof investment. Ethernet and parallel interfaces are available as options.

## Specifications

Model	CL-S400DT
Printing Technology	Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 - 4.6 inches (12.5 - 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 32 inches (6.35 to 812.8 mm)
Media Sensor	Fully adjustable gap, notch and reflective black mark
Main Interface	Dual Interface Serial (RS-232C), USB (version 2.0, full speed)
Optional interfaces	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant)
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons, 16x2 LCD with 2-colour backlight and sophisticated menu configuration system
Emulations (Languages)	Datamax® DMX, Cross-Emulation™ - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2®, CBI™ BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	8 MB total, 1 MB available for user

## CL-S400DT

### Label, Ticketing

### Features & Benefits

- Paper load: Durable design - Citizen's proven Hi-Lift™ all-metal mechanism
- Printing Speed: Fast print out - 6 inches per second (150 mm per second)
- Media support: Versatile Media Support - Fanfold media stacks and roll paper support
- Display: 2-colour LCD display enables intuitive operation
- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- Low space requirement - integrated power supply enables clean work station
- ENERGY STAR® compliant
- Small footprint



Compact footprint and metal mechanism

# CITIZEN

CL-S400DT

Label, Ticketing

<b>Model</b>	<b>CL-S400DT</b>
<b>Size (W x D x H) and Weight</b>	206 x 149 x 150mm, 2.68 Kg (excluding roll holder)
<b>Cutter</b>	Guillotine type, Dealer Installable

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0