

# The desktop printer that makes life easy

Versatile desktop printer

# 

# Fast print speed

Printing a typical courier label takes just one second with virtually instant first label printing.

### **Durable internal power supply**

All printers feature an internal mains power supply to provide the most reliable operation and avoid the problem of external power supplies.

# **Thermal transfer**

The CL?S621II is thermal transfer using a wide variety of ribbons to print on all media types.

# CL-S621II

# Label, Industrial Desktop

# Applications

- Courier
- E-Seller
- Healthcare
- Hospitality
- Logistic / Transport
- Manufacturing
- Pharmacy
- Retail



Desktop size - industrial performance.

# TOMORROW'S PRINTING TODAY

# CITIZEN

# Specifications

Model	CL-S621II
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi
Print Speed (maximum)	6 inches per second (150 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	0.5 - 4.6 inches (12.5 - 118 mm)
Roll Size (max), Core Size	Inside diameter 5 inches (125 mm) External diameter 8 inches (200mm) Core size 1 inch (25mm)
Media Thickness (min to max)	63.5 to 254 μm
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Media Sensor	Fully adjustable gap, notch and reflective black mark
Main Interface	Dual Interface Serial (RS-232C), USB (version 1.1)
Optional interfaces	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT), Parallel (IEEE 1284 compliant)
Ribbon size	2.9 inches (74mm) maximum outside diameter. 360 metres length. 1 inch (25mm) core
Ribbon winding & type	Ink side in or out, switch selectable. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head
Control panel	4 buttons and 4 LEDs
Emulations (Languages)	Datamax® DMX, Cross-Emulation <sup>™</sup> - autoswitch between Zebra® and Datamax® emulations, Zebra® ZPL2® , CBI <sup>™</sup> BASIC Interpreter, Eltron® EPL2®
Drivers and software	Free-of-charge on CD with printer, including support for various platforms

# CL-S621II

# Label, Industrial Desktop

# Features & Benefits

- Paper load: Durable design Citizen's proven Hi-Lift<sup>™</sup> all-metal mechanism
- Printing Speed: Fast print out 6 inches per second (150 mm per second)
- Media support: Large media capacity holds rolls up to 5 inches (127 mm)
- Ribbon options: Wide range of ribbon options - Uses up to 360 metres inside and outside wound ribbons
- Hi-Open<sup>™</sup> case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels the ARCP<sup>™</sup> ribbon control technology assures clear prints.
- Low space requirement integrated power supply enables clean work station
- ENERGY STAR® compliant
- Recyclable packacking
- Basic peeler

Citizen Systems Europe GmbH, Elizabeth House, 56-60 London Road, Staines-Upon-Thames, TW18 4HF, United Kingdom

# CITIZEN

Model	CL-S621II
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	231 x 289 x 270 mm, 4.5 Kg
Cutter	Guillotine type, Dealer Installable
Warranty	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0

# CL-S621II

# Label, Industrial Desktop